

TELEDYNE HASTINGS

DUAL SENSOR VACUUM GAUGE

INSTRUMENTS

OBE

FEATURES

- Low-Cost Electronics Module
- Wide Dynamic Range (1x10⁻⁴ - 1000 Torr)
- Combined Sensors in a Single Tube
- Input Voltage (12-30 VDC)
- 15-pin High-Density D-sub Connector
- Bright 4-Digit (green) LED Display
- Optional Outputs
 - Dual 0-10V
 - RS232/485
 - Dual 4-20 mA
 - DeviceNet™

APPLICATIONS

- Loadlock
- Plasma Coating
- OEM Equipment
- Wide Range Vacuum Controls
- Refrigeration



OBE

DESIGN FEATURES

OBE

The OBE is an electronics module which provides the user with a low-cost method of accurate vacuum measurement over a wide range of pressure. The OBE uses the same rugged HPM-2002S tube as the award-winning Model 2002®. The module contains all of the performance features of the Model 2002 dual sensor instrument in a compact configuration. The OBE electronics module is available with many different types of signal output options for the user.

OBE is ideal for applications that require accuracy without the expense of costly capacitance manometers and a wide measurement range without multiple gauges.

The OBE can be configured to provide one of several different output options. These include Dual 0-10 VDC, RS232, RS485, Dual 4-20 mA, or DeviceNet™. All output options, except DeviceNet™, include a 4-digit LED display. The display provides floating-point pressure readout which is easily visible from several meters.

The 0-10 VDC analog output version generates two outputs which are linear with pressure. The first output has a 1024 Torr full scale value; the second output has a 1000 mTorr full scale value.

A digital communication version provides either RS232 or RS485 output to the user's PC. A simple set of commands allows the user to configure and read the OBE. The RS485 configuration is capable of communication up to 4000 feet with up to 31 addressable instruments on the same bus.



TELEDYNE INSTRUMENTS
Hastings Instruments
A Teledyne Technologies Company

DESIGN FEATURES (cont)

Often used in industrial equipment, the dual 4-20 mA option gives the user two linear current outputs. The first 4-20 mA channel spans the pressure range to 1024 Torr full scale. The second channel spans to 1000 mTorr full scale.

A DeviceNet™ compatible version completes the available options for this wide range vacuum instrument. The DeviceNet™ protocol is a simple communications link to connect many different types of industrial devices to a network using standard hardware. This standard allows easy interchangeability among line products. The HPM-2002-OBE with DeviceNet™ has been fully tested and has earned the “DeviceNet Conformance Tested Service Mark”.

HPM-2002S Tube

The Model 2002 sensors are mounted in a rugged corrosive resistant 316 stainless steel tube. The small packaging reduces the transducer’s internal volume, significantly improving response time. The tube can be mounted in any orientation with no effect on calibration and is far more rugged than standard fragile convection driven Pirani tubes.

The two sensors are packaged on a single Au-plated Kovar header. This header is welded into the stainless steel tube shell and will withstand positive pressure to 150 psi.

Each HPM-2002S transducer contains a programmable memory chip (EEPROM). Stored on the EEPROM are the calibration parameters for both the thin film Pirani and the piezoresistive bridge.

Diagnostic Tube


The HPM-2002-DIAG allows users to verify proper operation of the HPM-2002 control unit and cabling. This diagnostic tube contains the same electronics as an HPM-2002S tube, however both sensors are replaced with known resistive loads. This allows a simulation of the voltage and power levels obtained in the crossover range of the two sensors, thereby causing the controller to indicate a pressure level of approximately 15 Torr. An EEPROM memory chip is also active within the diagnostic tube, allowing verification that the control unit can read the sensor’s memory data. (Note: There is no calibration information stored in the control unit. All coefficients are stored in the individual sensor; therefore, the diagnostic tube cannot be used in any way as a calibration device.)

SPECIFICATIONS




Measuring Range	1x10 ⁻⁴ to 10 ³ Torr
Ambient Temperature	0 to 50°C
Operating Range & Compensation	
Accuracy (Based on N ₂ @ 23°C)	± 1.5% of reading (1000 to 50 Torr) ± 15% of reading (50 to 1x10 ⁻³ Torr)
Output Options (choose one)	Dual (0-10 VDC linear), Dual (4-20 mA), RS232, RS485, DeviceNet™
Digital Readout	4-digit LED Floating Point
Input Voltage	12-30 VDC
Stability with Voltage Variation	Undetectable change in reading as input power fluctuates
Weight (approx.)	12 oz (w/ 1/8" NPT sensor)
Response Time	200 msec
Sensor Mounting	Any position without recalibration
Sensor Internal Volume	< 1.5 cc
Wetted Materials	Silicon Nitride, Silicon, Gold, Pyrex, 316 SS, UHV Epoxy
Calibrated for Nitrogen	Conversion curves for other gases are easily selectable
Positive Pressure	150 psig max. (Recalibration may be required if tube is exposed to pressures greatly exceeding measuring range.)

Teledyne Hastings Instruments reserves the right to change or modify the design of its equipment without any obligation to provide notification of change or intent to change.

OBE Analog Version



OBE RS232/485 Version



Note: Envelope approx. 3" diameter cylinder by 3" high, excluding sensor.
 All dimensions shown are in inches [mm].

Selection Chart

Typical instrument ordering/options number:

Model No.	Output	Display	Calibration	Gas	Units
OBE	00	01	00	00	00

Order No.	Options
Output	
00	Dual Analog 0-10 Volt (Standard)
01	RS 232
02	RS 485 2-wire Half Duplex
03	RS 485 2-wire Full Duplex
04	Dual 4-20 mA
05	Device <i>Net</i>
Display	
01	With Display (Standard)
Calibration	
00	Standard
01	NIST Certificate
02	Custom

Diagnostic Tube Order Information

Model
HPM-2002-DIAG

Order No.	Options
Gas	
00	Nitrogen (Standard)
01	Argon
02	Helium
03	Water Vapor
04	Custom
Units	
00	Torr (Standard)
01	mbar
02	Pascal

Typical instrument ordering/options number:

Model No.	System Connection
HPM-2002S	01

Order No.	Options
System Connection	
01	1/8" NPT (Standard)
02	1/4" VCR™
03	1.33 Mini Conflat™
04	2.75 Conflat™
05	KF-16™
06	KF-25™
07	1/2" O.D. Smooth Tube
08	1/2" VCR

Your Customer Service Representative



TELEDYNE INSTRUMENTS

Hastings Instruments
A Teledyne Technologies Company

Telephone: (757) 723-6531
Toll Free: (800) 950-2468
Fax: (757) 723-3925
World Wide Web: <http://www.teledyne-hi.com>
E-mail: hastings_instruments@teledyne.com
P.O. Box 1436
Hampton, VA 23661